

CSA Aluminum Flexible Conduit



APPLICATION:

CSA Aluminum Flexible Conduit allows electrical contractors to run hundreds of feet of conduit without installing connectors between sections of conduit or the need for frequent braces to support the weight.

CONSTRUCTION:

- Light weight, primary, tempered aluminum alloy provides maximum strength and flexibility. Superior resistance to corrosion with a smooth interior for easy pull through. Built in flexibility provides easy installation. 1/3 weight of steel

STANDARDS:

- CSA Approved
- ROHS

Part Number	Trade Size	Inside Diameter Min.	Outside Diameter Max	Bending Diameter	Weight
	inches	inches	inches	inches	kg/m
CSAAF3/8	3/8"	0.375	0.510	3.5	0.088
CSAAF7/16	7/16"	0.437	0.675	4.5	0.105
CSAAF1/2	1/2"	0.625	0.920	6.0	0.245
CSAAF3/4	3/4"	0.812	1.105	8.0	0.313
CSAAF1	1"	1.000	1.380	10.0	0.481
CSAAF1-1/4	1-1/4"	1.250	1.630	12.5	0.578
CSAAF1-1/2	1-1/2"	1.500	1.950	15.0	0.660
CSAAF2	2"	2.000	2.450	20.0	0.876
CSAAF2-1/2	2-1/2"	2.500	3.060	25.0	1.180
CSAAF3	3"	3.000	3.560	30.0	1.265
CSAAF3-1/2	3-1/2"	3.500	4.060	35.0	1.465
CSAAF4	4"	4.000	4.560	40.0	1.693

All values are nominal and subject to correction.



1-877-611-5122
www.PriorityWire.ca



©2022 Priority Wire & Cable
 10-2022