



CSA Liquid-Tight

Trade Size	Part Number	Internal Diameter		External Diameter				Bend Diameter		Weight	
		Min		Min		Max		mm	inches	kg/m	lbs/100ft
		mm	inches	mm	inches	mm	inches				
CSA Liquid-Tight Standard Coil and Reels											
3/8"	CSALT3/8-30M	12.29	0.484	17.50	0.690	18.00	0.710	102	4.0	0.35	24
1/2"	CSALT1/2-30M	15.80	0.622	20.80	0.820	21.30	0.840	152	6.0	0.42	28
1/2"	CSALT1/2-300M	15.80	0.622	20.80	0.820	21.30	0.840	152	6.0	0.42	28
3/4"	CSALT3/4-30M	20.83	0.820	26.16	1.030	26.67	1.050	203	8.0	0.55	37
3/4"	CSALT3/4-300M	20.83	0.820	26.16	1.030	26.67	1.050	203	8.0	0.55	37
1"	CSALT1-30M	26.44	1.041	32.80	1.290	33.40	1.315	254	10.0	0.80	54
1-1/4"	CSALT1-1/4-15M	35.05	1.380	41.40	1.630	42.20	1.660	318	12.5	1.13	76
1-1/2"	CSALT1-1/2-15M	40.01	1.575	47.40	1.865	48.30	1.900	381	15.0	1.45	97
2"	CSALT2-15M	51.31	2.020	59.40	2.340	60.30	2.375	508	20.0	1.67	112

*All values are nominal and subject to correction

Application: CSALT provides lasting wiring protection on machine tools, portable tools, presses, welders, pumps, blowers, grinders, conveyors, heating equipment, and automated lines for forging, plating, molding blasting, rolling, die casting, processing, extruding, etc. As well as providing wiring protection in many other applications in the industrial and commercial sectors.

Construction: Black PVC jacket over a galvanized steel inner core.

Standards: CSA Approved, FT-4 Rated.
Sunlight resistant, corrosion resistant.
Temperature range: -20°C to +75°C.

1-877-611-5122