

PVC Thermostat Cable 150V 60°C



APPLICATION:

PVC Thermostat Cable is primarily used for power limited circuits such as thermostats, air conditioning, heat pumps, bell and alarm systems, signals systems, door bells and remote control units where the voltage does not exceed 150 volts. Temperature rating is -20°C to +60°C.

CONDUCTORS:

- Solid soft drawn copper, per ASTM B3 and B258

INSULATION:

- Heat and moisture resistant colored polyvinyl chloride (PVC) insulation

JACKET:

- Outer jacket of polyvinyl chloride (PVC), which is heat, moisture and sunlight resistant
- Available in either Brown or White

STANDARDS:

- CSA C22.2 No. 214/UL 444
- C(UL) listed, CM
- UL listed CL2
- Sunlight resistant

COLOR CODE:

Cond #	Color	Cond #	Color	Cond #	Color
1	White	5	Yellow	9	Purple
2	Red	6	Brown	10	Gray
3	Green	7	Orange	11	Pink
4	Blue	8	Black	12	Tan

Part Number**	AWG	No. of Conductors	Construction	Wall Thickness		Nominal Overall Diameter	Weight
				Insulation	Jacket		
				inches	inches	inches	lbs/1000'
18-02TSTAT	18	2	Parallel	0.006	0.015	0.136	15
18-03TSTAT	18	3	Cabled	0.006	0.015	0.144	21
18-04TSTAT	18	4	Cabled	0.006	0.015	0.158	27
18-05TSTAT	18	5	Cabled	0.006	0.015	0.174	34
18-06TSTAT	18	6	Cabled	0.006	0.015	0.184	40
18-07TSTAT	18	7	Cabled	0.006	0.015	0.190	45
18-08TSTAT	18	8	Cabled	0.006	0.015	0.208	51
18-09TSTAT	18	9	Cabled	0.006	0.015	0.224	57
18-10TSTAT	18	10	Cabled	0.006	0.015	0.227	63
18-12TSTAT	18	12	Cabled	0.006	0.015	0.245	74

All values are nominal and subject to correction.

**Add BR for Brown or WH for White jacket color

1-877-611-5122
www.PriorityWire.ca



PVC Thermostat Cable

150V 60°C



Part Number**	AWG	No. of Conductors	Construction	Wall Thickness		Nominal Overall Diameter	Weight
				Insulation	Jacket		
				inches	inches	inches	lbs/1000'
20-02TSTAT	20	2	Parallel	0.006	0.015	0.117	11
20-03TSTAT	20	3	Cabled	0.006	0.015	0.124	15
20-04TSTAT	20	4	Cabled	0.006	0.015	0.135	20
20-05TSTAT	20	5	Cabled	0.006	0.015	0.148	24
20-06TSTAT	20	6	Cabled	0.006	0.015	0.156	27
20-07TSTAT	20	7	Cabled	0.006	0.015	0.161	31
20-08TSTAT	20	8	Cabled	0.006	0.015	0.175	35
20-09TSTAT	20	9	Cabled	0.006	0.015	0.189	39
20-10TSTAT	20	10	Cabled	0.006	0.015	0.191	43
20-12TSTAT	20	12	Cabled	0.006	0.015	0.206	53
22-02TSTAT	22	2	Parallel	0.006	0.015	0.104	9
22-03TSTAT	22	3	Cabled	0.006	0.015	0.110	11
22-04TSTAT	22	4	Cabled	0.006	0.015	0.120	15
22-05TSTAT	22	5	Cabled	0.006	0.015	0.130	17
22-06TSTAT	22	6	Cabled	0.006	0.015	0.138	19
22-07TSTAT	22	7	Cabled	0.006	0.015	0.142	22
22-08TSTAT	22	8	Cabled	0.006	0.015	0.154	25
22-09TSTAT	22	9	Cabled	0.006	0.015	0.165	27
22-10TSTAT	22	10	Cabled	0.006	0.015	0.168	30
22-12TSTAT	22	12	Cabled	0.006	0.015	0.180	34

All values are nominal and subject to correction.

**Add BR for Brown or WH for White jacket color



1-877-611-5122
www.PriorityWire.ca



©2024 Priority Wire & Cable
 09-2024